

References

- [1] Adams R J and Hannaford B 1999 Stable Haptic Interaction with Virtual Environments. *IEEE Trans. Rob. Automat.* 15(3):465–474
- [2] Adams R J, Moreyra M R and Hannaford B., “Stability and performance of haptic displays: theory and experiments. *Proc. Int. Mech. Engg. Congr. Exp.*, pp. 227-234, Anaheim, CA, 1998.
- [3] Anderson R J and Spong M W 1989 Bilateral control of operators with time delay. *IEEE Trans. Automat. Contr.* 34:494–501
- [4] Andriot C A and Fournier R 1992 Bilateral Control of Teleoperators with Flexible Joints by the H^∞ Approach. In *Proc. SPIE Conf. 1933: Telemanipulator Technology*. pp 80–91
- [5] Boyd S P and Barratt C H 1991 *Linear Controller Design: Limits of Performance*. Prentice Hall, Englewood Cliffs, New Jersey
- [6] Brown J M and Colgate J E 1997 Passive Implementation of Multibody Simulations for Haptic Display. In *Proc. Int. Mech. Engg. Congr. Exp.*, Dallas, TX.
- [7] Chang B and Colgate J E 1997 Real-Time Impulse-Based Simulation of Rigid Body Systems for Haptic Display. *Proceedings of the 1997 ASME International Mechanical Engineering Congress and Exhibition*, pp. 1-8.
- [8] Chen W K 1980 Active Network and Feedback Amplifier Theory. McGraw-Hill.
- [9] Colgate J E and Hogan N 1988 Robust control of dynamically interacting systems. *International Journal of Control*. 48(1):65-88
- [10] Colgate J E 1993 Robust Impedance Shaping Telemanipulation. *IEEE Trans. Robot. Automat.* 9:374–384
- [11] Colgate J E, Brown J M, “Factors affecting the Z-Width of a Haptic Display”, in *Proc. IEEE Int. Conf. Rob. Aut.*, pp. 3205-3210, 1994.
- [12] J.E. Colgate, P.E. Grafting, M.C. Stanley and G. Schenkel. ”Implementation of Stiff Virtual Walls in Force-Reflecting Interfaces”, in *Proc. IEEE VR Annual Symposium*, pp. 202-208, Seattle, WA, 1993.
- [13] D. Constantinescu, I. Chau, S.P. DiMaio, L. Filipozzi, S.E. Salcudean and F. Ghassemi, ”Haptic Rendering of Planar Rigid-Body Motion using a Redundant Parallel Mechanism”, 2000 IEEE International Conference on Robotics and Automation San Francisco, CA, April 2000.
- [14] Gillespie R B and Colgate J E 1997 A Survey of Multibody Dynamics for Virtual Environments. In *Proc. Int. Mech. Engg. Congr. Exp.*, Dallas, TX.

- [15] Gillespie R B and Cutkosky M R 1993 Interactive Dynamics with Haptic Display. In *Advances in Robotics, Mechatronics, and Haptic Interfaces, ASME Winter Annual Meeting*, DSC-49, pp. 65-72.
- [16] Gillespie R B and Cutkosky M R. "Stable User-Specific Haptic Rendering of the Virtual Wall", *Proc. ASME DSC-58*, pp.397-406, 1996.
- [17] Goldfarb, M. and Wang, J. "Passive Stiffness Simulation with Rate-Independent Hysteresis", *Proc. Int. Mech. Engg. Congr. Exp.*, vol DSC-67, pp345-350, Nashville, TE, 1999.
- [18] Hacksel P and Salcudean S E 1994 Estimation of Environment Forces and Rigid-Body Velocities Using Observers. In *Proc. IEEE Int. Conf. Robot. Automat.*, San Diego, CA, pp 931-936
- [19] Hannaford B 1989 A Design Framework for Teleoperators with Kinesthetic Feedback. *IEEE Trans. Robot. Automat.*. 5:426-434
- [20] K. Hashtrudi Zaad and S.E. Salcudean, "Adaptive Transparent Impedance Reflecting Teleoperation", Proceedings of the 1996 IEEE International Conference on Robotics and Automation, pp.1369-1374, April 22-28, 1996, Minneapolis, Minnesota.
- [21] K. Hashtrudi-Zaad and S.E. Salcudean, "Analysis and Evaluation of Stability and Performance Robustness for Teleoperation Control Architectures", 2000 IEEE International Conference on Robotics and Automation, San Francisco, CA, April 2000.
- [22] K. Hashtrudi-Zaad and S.E. Salcudean, "On the Use of Local Force Feedback for Transparent Teleoperation", IEEE International Conference on Robotics and Automation, pp.1863-1869, Detroit, MI, May 1999.
- [23] Haykin S S 1970 Active Network Theory. Addison-Wesley.
- [24] Hu Z, Salcudean S E and Loewen P D, 1996 Optimization-based teleoperation controller design. In *Proc. 13th IFAC World Congress, Vol. D*, San Francisco, CA, pp 405-410
- [25] Kazerooni H, Tsay T-I and Hollerbach K 1993 A Controller Design Framework for Telerobotic Systems. *IEEE Trans. Contr. Sys. Tech.* 11:105-116
- [26] Lawn C A and Hannaford B 1993 Performance Testing of Passive Communications and Control in Teleoperation with Time Delay. In *Proc IEEE Int. Conf. Rob. Automat.*, San Diego, CA, pp 776-783
- [27] Lawrence D A 1993 Stability and Transparency in Bilateral Teleoperation. *IEEE Trans. Robot. Automat.*. 9:624-637

- [28] D.A. Lawrence, J.D. Chapel, "Performance Trade-Offs for Hand Controller Design," 1994, , Proc. IEEE International Conference on Robotics and Automation, May, pp. 3211-3216.
- [29] Leung G M H, Francis B A, and Apkarian A 1995 Bilateral controller for teleoperators with time delay via μ -synthesis. *IEEE Trans. Robot. Automat.*. 10:105–116
- [30] Llewellyn F B 1952 Some Fundamental Properties of Transmission Systems. *Proc. I.R.E.* 40:271
- [31] M. Minsky, M. Ouh-young, O. Steele, F.P.Jr. Brooks, and M. Behensky. Feeling and Seeing: Issues in Force Display. *Comp. Graph.*, 24(2):235–243, 1990.
- [32] Nahvi A, Hollerbach J M, Freier R and Nelson D D , 1998 Display of Friction in Virtual Environments based on Human Finger Pad Characteristics. In *Proc. Int. Mech. Engg. Congr. Exp.*, DSC-64, pp.179-184.
- [33] A. Nahvi, D.D. Nelson, J.M. Hollerbach, and D.E. Johnson. Haptic Manipulation of Virtual Mechanisms from Mechanical CAD Designs. In *Proceedings of the 1998 IEEE International Conference on Robotics and Automation*, pages 375–380, Leuven, Belgium, May 1998.
- [34] S. Nicosia and P. Tomei. Robot control by using only joint position measurements. In *IEEE Transactions on Automatic Control*, pages 1058–1061, September 1990.
- [35] Niemeyer G and Slotine J J E, 1991 Stable Adaptive Teleoperation. *IEEE J. Oceanic Engg.* 16:152–162
- [36] Reboulet C, Plihon Y, and Briere Y 1995 Interest of the dual hybrid control scheme for teleoperation with time delays. In: Khatib O, Salisbury J K (eds), *Experimental Robotics IV*, Springer Verlag, pp 498–506
- [37] S.E. Salcudean, M. Wong, and R.L. Hollis. Design and Control of a Force-Reflecting Teleoperation System with Magnetically Levitated Master and Wrist. In *IEEE Trans. on Robotics and Automation*, volume 11, December 1995.
- [38] Salcudean S E and Vlaar T 1994 On the Emulation of Stiff Walls and Static Friction with a Magnetically Levitated Input-Output Device. In *Proc. ASME Int. Mech. Eng. Congr. Exp., DSC-Vol. 55-1*, Chicago, IL pp 303–309
- [39] Salcudean S E 1997 Control for teleoperation and haptic interfaces. In *Control problems in robotics and automation*, B. Siciliano and K.P. Valavanis (Eds), pp. 51–66, Springer-Verlag LNCIS Vol. 230.

- [40] S.E. Salcudean, R. Six, R. Barman, S. Kingdon, I. Chau, D. Murray and M. Steenburgh, "Control Electronics and Hybrid Dynamic Systems-based API for a 6-DOF Desktop Haptic Interface", 1999 Symposium on Haptic Interfaces for Virtual Environments and Teleoperation Systems, Intl. Mech. Eng. Congr. Exp., (ASME Winter Annual Meeting), DSC Vol., pp.407-414, Nashville, TN, November 1999.
- [41] S.E. Salcudean, K. Hashtrudi-Zaad, S. Tafazoli, S.P. DiMaio, and C. Reboulet, "Bilateral Matched-Impedance Teleoperation with Applications to Excavator Control", Control Systems Magazine, Vol.19, No.6, pp.29-37, December 1999.
- [42] M.R. Sirouspour, S.P. DiMaio, S.E. Salcudean, P. Abolmaesumi and C. Jones, "Haptic Interface Control - Design Issues and Experiments with a Planar Device", 2000 IEEE International Conference on Robotics and Automation, San Francisco, CA, April 2000.
- [43] Strassberg Y, Goldenberg A A and Mills J K 1993 A New Control Scheme for Bilateral Teleoperating Systems: Stability and Robustness Analysis. *ASME J Dyn. Sys. Meas. Contr.* 3:345-351
- [44] Wen J T 1988 Robustness Analysis Based on Passivity. In *Proc. American Control Conference*, Atlanta, GA, pp 1207-1212
- [45] Yan J and Salcudean S E, 1996 Teleoperation Controller Design using H^∞ Optimization. *IEEE Trans. Contr. Sys. Tech.* 4:244-258
- [46] Yokokohji Y and Yoshikawa T 1994 Bilateral Control of Master-Slave Manipulators for Ideal Kinesthetic Coupling. *IEEE Trans. Robot. Automat.* 10:605-620
- [47] T. Yoshikawa and H. Uead. Construction of Virtual World Using Dynamics Modules and Interaction Modules. In *Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, pages 2358-2364, Minneapolis, Minnesota, 1996.
- [48] Zhu M and Salcudean S E 1995 Achieving Transparency for Teleoperator Systems under Position and Rate Control. In *Proc. IEEE/RSJ Int. Conf. Intelli. Robots Sys. (IROS'95)*, Pittsburgh, PA, pp 7-12
- [49] W.H. Zhu and S.E. Salcudean "Stability-guaranteed Teleoperation: An adaptive Motion/Force Control Approach", IEEE Transactions on Automatic Control, November 2000, in press.